

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

4-14-1957

Test 612: McCormick Farmall 450 Gasoline

Tractor Test & Power Museum

University of Nebraska, jsteele4@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Museum, Tractor Test & Power, "Test 612: McCormick Farmall 450 Gasoline" (1957). *Nebraska Tractor Tests*. 7.

<https://digitalcommons.unl.edu/tractormuseumlit/7>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

Department of Agricultural Engineering
Dates of test: April 9, 1957 to April 14, 1957
Manufacturer: INTERNATIONAL HARVESTER
COMPANY, CHICAGO 1, ILLINOIS
Manufacturer's rating: Not Rated

NEBRASKA TRACTOR TEST NO. 612

McCORMICK FARMALL 450

BELT HORSEPOWER TESTS

Hp	Crank shaft speed rpm	Fuel Consumption			Temp. Deg. F.			Barometer inches of mercury		
		Gal per hr	Hp-hr per gal	Lb per hp-hr	Cooling medium	Air wet bulb	Air dry bulb			
TEST B—100% MAXIMUM LOAD—TWO HOURS										
55.28	1450	4.824	11.46	0.528	158	47	62	29.045		
TEST C—OPERATING MAXIMUM LOAD—ONE HOUR										
51.55	1450	4.134	12.47	0.485	158	49	64	29.153		
TEST D—RATED LOAD—ONE HOUR										
48.58	1450	3.977	12.22	0.495	154	48	61	29.148		
TEST E—VARYING LOAD—TWO HOURS (20 minute runs; last line average)										
48.60	1450	3.968	12.25	0.494	153	47	60		
1.22	1634	1.488	0.82	7.377	193	46	59		
26.47	1574	2.788	9.49	0.637	183	50	67		
50.27	1401	4.003	12.56	0.482	175	50	64		
13.64	1618	2.118	6.44	0.939	186	48	63		
38.99	1548	3.502	11.13	0.543	155	52	70		
29.87	1537	2.978	10.03	0.603	174	49	64	29.155		
TEST L—OPERATING MAXIMUM TORQUE										
% of rated rpm (engine)	100	95	90	85	80	75	70	65	60	55
% of rated-speed torque	100	102	104	106	109	112	114	115	114	114

DRAWBAR HORSEPOWER TESTS

Hp	Draw bar pull lbs	Speed miles per hr	Crank shaft speed rpm	Slip of drive wheels %	Fuel Consumption			Temp. Deg. F.			Barometer inches of mercury
					Gal per hr	Hp-hr per gal	Lb per hp-hr	Cool- ing med	Air wet bulb	Air dry bulb	
TEST H—RATED LOAD—TEN HOURS—3rd Gear											
38.55	3079	4.70	1452	4.04	3.687	10.46	0.578	168	26	30	29.328
TEST F—100% MAXIMUM LOAD											
51.25	4142	4.64	1452	5.19	3rd gear	175	29	36	29.220
TEST G—OPERATING MAXIMUM LOAD											
41.94	7307	2.15	1451	14.97	1st gear	141	26	28	29.290
46.46	4784	3.64	1453	6.80	2nd gear	144	30	34	29.320
47.64	3826	4.67	1454	4.78	3rd gear	165	29	36	29.220
46.57	2654	6.58	1450	3.18	4th gear	164	29	36	29.220
41.07	923	16.69	1449	1.00	5th gear	148	33	39	29.290
28.14	7318	1.44	1447	15.30	1st gear TA (prt-thrtl)	141	29	31	29.280
41.59	6949	2.24	1455	14.97	2nd gear torc amplifier.	143	30	34	29.320
44.81	5545	3.03	1451	8.16	3rd gear torc amplifier.	146	33	39	29.290
46.13	3958	4.37	1452	4.92	4th gear torc amplifier.	163	30	35	29.220
43.78	1472	11.15	1449	2.17	5th gear torc amplifier.	146	33	39	29.290
TEST J—OPERATING MAXIMUM LOAD											
44.45	3779	4.41	1455	11.29	3rd gear	152	37	45	29.210
TEST K—OPERATING MAXIMUM LOAD											
44.73	4000	4.19	1463	11.67	3rd gear	150	39	47	29.210

TIRES, WHEELS AND WEIGHT

	Tests F, G, & H	Test J	Test K
Rear wheels			
Type	Cast Iron	Cast Iron	Cast Iron
Liquid ballast	690 lb each	None	None
Added cast iron	560 lb each	None	None
Rear tires			
No. and size	Two 15.5-38	Two 15.5-38	Two 11-38
Ply	6	6	4
Air Pressure	18 lb	14 lb	14 lb
Front wheels			
Type	Cast Iron	Cast Iron	Cast Iron
Liquid ballast	None	None	None
Added cast iron	None	None	None
Front tires			
No. and size	Two 6.00-16	Two 6.00-16	Two 6.00-16
Ply	4	4	4
Air pressure	28 lb	28 lb	28 lb
Height of drawbar	22½ inches	23 inches	21½ inches
Static weight			
Rear end	7020 lb	4520 lb	4306 lb
Front end	1830 lb	1824 lb	1822 lb
Total weight as tested with operator	9025 lb	6519 lb	6303 lb

FUEL, OIL, WATER and TIME Fuel Gasoline Octane No. ASTM 82 Research 88 (rating taken from oil company's typical inspection data) Weight per gallon 6.048 lb Oil SAE 20-20W To motor 2.011 gal Drained from motor 1.720 gal Water used 0.175 gal Total time motor was operated 41½ hours.

CHASSIS TYPE Tricycle Serial No. 1751 S Tread width rear 50" to 94" Front 8½" to 17½" Wheel base 95¾" Hydraulic control system direct engine drive Advertised speeds mph first 2.5 second 3.8 third 4.8 fourth 6.7 fifth 16.6 reverse 3.3 (using torque amplifier) first 1.7 second 2.6 third 3.2 fourth 4.5 fifth 11.2 reverse 2.2 Belt pulley diam. 11" face 7½" rpm 899 Belt speed 2588 fpm Belt flat Length 72" Width 7" Thickness 0.216" Maximum slip 1.01% Clutch single plate dry disc operated by foot pedal Seat upholstered seat on conical spring with shock absorber Brakes double disc brakes operated by two foot pedals Equalized by locking pedals together Power take-off direct engine drive with independent clutch Steering hydraulically aided.

ENGINE Make International Type 4 cylinder vertical Serial No. 1645 Crankshaft mounted lengthwise Head 1 Lubrication pressure Bore and stroke 4⅛" x 5¼" Rated rpm 1450 Compression ratio 6.6 to 1 Displacement 281 cu. in. Port diameter valves Inlet 1 19/32" Exhaust 1 7/16" Governor variable speed centrifugal Carburetor size 1¼" Ignition system battery Starting system 6 volt battery Air cleaner oil washed wire mesh Muffler was used Oil filter replaceable treated paper element Cooling medium temperature control thermostat and radiator shutter.

REPAIRS AND ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum belt horsepower and data from these tests were used in determining the horsepower to be developed in tests D and H, respectively. Tests C, D, E, G, H, J, K and L were made with an operating setting of the carburetor (selected by the manufacturer) of 93.1% of maximum belt horsepower.

HORSEPOWER SUMMARY

	Drawbar	Belt
1. Sea level (calculated) maximum horsepower (based on 60° F and 29.92" Hg)	51.25	57.05
2. Observed maximum horsepower (tests F and B)	51.25	55.28
3. Seventy-five per cent of calculated maximum drawbar horsepower and eighty-five per cent of calculated maximum belt horsepower (ASAE and SAE ratings)	38.44	48.49

We, the undersigned, certify that this is a true and correct report of official Tractor Test No. 612.

L. F. LARSEN

Engineer-in-Charge

L. W. HURLBUT (Chairman)

G. W. STEINBRUEGGE

J. J. SULEK

Board of Tractor
Test Engineers

EXPLANATION OF TEST REPORT

TEST A: The manufacturer's representative operates the tractor for a minimum of 12 hours using light to heavy drawbar loads in each gear.

This serves as a period for limber up, general observation and adjustments. Adjustments that are permissible include valve tappet clearance, breaker point gap, spark plug gaps, clutch and others of a similar nature. No new parts or accessories can be installed without having mention made of it in the report.

No data are recorded during this preliminary run except the time that the engine is operated.

BELT HORSEPOWER TESTS

TEST B: The throttle valve is wide open and the belt load on the dynamometer is adjusted so that the engine is at the rated speed recommended by the manufacturer. Carburetor, ignition timing and manifold adjustments are all set for maximum engine power.

This test is designed to determine maximum belt horsepower of the tractor at rated speed and to measure fuel consumption at the maximum power on the belt.

TEST C: For tractors with carburetors the best fuel economy does not always occur when the engine develops maximum power at rated speed. Test C is intended to allow the manufacturer's representative to select a more economical fuel setting even though there is a slight loss of power. *This more practical carburetor setting is used in all later tests except test F.* The throttle valve is wide open and load adjusted to give rated rpm. Tests B and C are the same for diesel tractors which have an altogether different fuel system.

TEST D: The throttle control lever is set so that the governor will maintain rated engine speed when rated load is applied. Rated load is 85% of 100% maximum, as obtained in test B, corrected to standard conditions.

This rating is somewhat less than the maximum belt horsepower in order that the operator may have a certain amount of reserve.

TEST E:

Varying load serves to show the range of engine speeds when the engine is controlled by the governor during the following varied loads, of 20 minutes each; rated load, no load, $\frac{1}{2}$ rated load, maximum load at wide open throttle valve, $\frac{1}{4}$ and $\frac{3}{4}$ rated load.

The average result of this test shows the average power and fuel consumption. Since the average tractor is subjected to varying loads, these data serve well in predicting fuel consumption and efficiency of a tractor in general use.

TEST L: This torque test is run with wide open throttle. Loads are applied to reduce engine speed in approximately ten 5% increments. Rated speed equals 100%. The corresponding dynamometer torque is recorded as a per cent of torque at rated speed.

DRAWBAR HORSEPOWER TESTS

In all drawbar tests the pull exerted by the tractor is transmitted by a hydraulic pressure cylinder to a recording instru-

ment in the test car. When rubber tires are used, all tests are made on the concrete test course. All crawler type tractors are tested on a dirt test course which is maintained by grading, sprinkling and rolling so that it remains very nearly the same throughout the season. The same tires, wheels and weights are used for all tests except J and K.

TEST F: A drawbar test, the results of which are used to determine the rated drawbar horsepower in test H. The carburetor is set to develop maximum power as in test B. The rated gear recommended by manufacturer as plow gear is used in this test. The drawbar load is adjusted to give rated engine speed.

TEST G: Maximum drawbar horsepower is determined in each gear when the carburetor is set for fuel economy as in test C. The throttle valve is held wide open and the load is applied so that the engine runs at rated engine speed.

When operating in low gear it is not uncommon for the tractor to develop less drawbar horsepower than in rated gear because of excessive wheel slippage. When excessive wheel slippage occurs the load is reduced until slippage approaches 16%. When the load is reduced it is necessary to operate the tractor engine at part throttle and control engine speed by governor action.

TEST H: Intended to test the ability of the tractor to run continuously for 10 hours at rated drawbar horsepower and to determine the fuel consumption during that time. Rated drawbar horsepower is 75% of 100% maximum drawbar horsepower (Test F), corrected to standard conditions.

When operating at rated load the throttle control lever is set to maintain rated engine speed. This rating is less than maximum drawbar horsepower in order that the operator may have a certain amount of reserve.

TEST J: The tractor is operated in rated gear with all added weight removed. This test shows the effect of the removal of added weight on the performance of the tractor when compared with test G.

Removal of wheel weights generally increases wheel slippage and decreases drawbar horsepower.

TEST K: Similar to test J except that the smallest tires and lightest wheels offered by the manufacturer are used.

